

B&E Technologies

FE-130T / FE-130C 100FX Fiber Fast Ethernet Adapter for PCI Bus

These are 32-bit Bus Mastering Fiber Optic Fast Ethernet Adapters for the PCI bus. They support 100Mbps Fast Ethernet connections over distances of up to 2 km and jumperless Plug and Play configuration. The adapter is supplied with a QNX 4 network driver. A QNX network boot ROM is also available. Users have a choice of ST or SC connectors.

Adapter Features

- 32-bit bus mastering PCI 2.0 bus
- 100Mbps transmission rate
- Full or half duplex
- I/O Mapped (set by PCI BIOS)
- Interrupts (set by PCI BIOS)
- ROM: Optional Boot ROM
- PnP jumperless configuration by PCI bus
- QNX 4 network driver on the adapter driver diskette



Operating Environment

- Power: +5V DC @ 500mA max
- Operating Temperature: 0°C to 40°C
- Storage Temperature: -40°C to 70°C
- Operating Humidity: 10% to 90% (non-condensing)
- Storage Humidity: 5% to 90% (non-condensing)

Warranty

- 2 years

B&E TECHNOLOGIES
8 Victoria Glen Street
Elmira, Ontario Canada
N3B 1S1
Phone: 519 669 0950
Fax: 519 669 2880
info@betech.biz
www.betech.biz